

RAM	2MB + 2MB DRAM
Interface	PCX, BMP, FLASH, DRAM
Barcode	CODE128, EAN128, ITF, Code39, Code93, EAN13, EAN13 + 2, EAN13 + 5, EAN8, EAN8 + 2, EAN8 + 5, CODABAR, POS TNET, UPC-A, UPCA + 2, UPCA + 5, UPC-E, UPCE + 2, UPCE + 5, C, POS T, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR, DATMATRIX
Connectivity	USB + RS232 + LAN, USB
Power	24VDC, 2.5A
Operating Conditions	5°C ~ 45°C -40°C ~ 55°C 20% ~ 80% Humidity ≤ 93% @ 40°C
Dimensions	D220mm * H148mm * W150mm

Features



Installation







OCBP-005





OCBP-005







3. 3.

OCOM

500 100

12 + 1 24

30 DOA DOA

4. 4.

T / T LC Western Union Escrow T / T Western Union Escrow Paypal Escrow Alipay.com Moneybookers Visa MasterCard Maestro Solo Carte Bleue Pos tePay CartaSi 4B Euro6000

5. 5.

6. 6.

Eruopean

133 1300 O2 500 50

OCOM

500 POS

O2 Star

1500 133

9 OEM / ODM

POS

FCC CE Soncap POA BIS

12 + 1

“ ”