

# 3

## OCBP-M80

- 1.
- 2.
- 3.
4. LCD
- 5.
- .

	80/ /
	70/ /
	8/ mm
	576/ /
	72/ /48/ /37.5
	ASCII/GB18030/BIG5
	12 * 24; B 8 * 16
	/
	80/ /58/ /44
	40
	13
	0.06/0.16
TPH	50
	EAN-13/EAN-8/UPC-A/UPCZ/CODE39/CODE93/CODE128/CODABAR/25 PDF417/QR CODE
	CPCL / ESC-POS
	Windows 98 / ME / 2000 / NT / XP / 2003/ VISTA / Win7/8
	USB /
	512KB; RAM 128KB
	32K
SDK	Windows CE; Windows Mobile 5.0 / 6.0; Symbian; Android
	46
	DC9V / 2A

電圧	7.4V 1.65A
容量	360mAh
充電時間	約3時間
充電電圧	3.6V
充電電流	196mA
充電電圧	3.6V (充電電圧); 充電電流
充電電圧 WxLxH	104mm x 109mm x 48mm
充電電圧	充電電圧
充電電圧	-10-50°C
充電電圧	10-80%
充電電圧	充電電圧
充電電圧	充電電圧 USB 充電電圧
充電電圧	充電電圧
充電電圧	210mm x 155mm x 90mm 1.5mm

× × × × × × × × × × × × × × × ×