

32 OCBS-W800

OCBS-W800

32mm x 168mm x 130mm
 32mm x 72mm x 45mm
 200MHz
 100mm
 750mAh

OCBS-W800

OCBS-W800 CHARACTERISTICS	
OCBS-W800	VLD @ 650nm
OCBS-W800 (mm)	168mm * 72mm * 93mm W * H * D
OCBS-W800 (mm)	130mm * 45mm * 129mm W * H * D
OCBS-W800	ABS + TPR /mm
OCBS-W800	370mm
OCBS-W800	mm;mm
OCBS-W800	LEDmm
OCBS-W800	mmmm
OCBS-W800 CHARACTERISTICS	
OCBS-W800	60mm @ 30mm 98mm @ 100mm
OCBS-W800	10-450mmmm0.9mm0.25mm
OCBS-W800	150mm/mm
OCBS-W800	0.10-0.825mm
OCBS-W800	1 /mm500mm
OCBS-W800	UPC / EANmmUPC / EANmmmmUCC / EAN128mm39mm39mmASCIImmTrioptic 39mm128mm128mmASCIImmmm5mm2mm2 5mm93mmmm11mmRSSmm5mmMSI / PlesseymmUK / PlesseymmUCC / EAN 128mmmmmmGS1mmDataBarmmRSSmmmmmm2
OCBS-W800	3.7V / 750mAhmmmm
OCBS-W800	3.0mm
OCBS-W800	30mm
OCBS-W800	95mmmmmm; 25mmmmmm
OCBS-W800	mm60°;mm45°
OCBS-W800	433MHzmm
OCBS-W800	200mmmmmmmm
OCBS-W800	USB
OCBS-W800 CHARACTERISTICS	
OCBS-W800	-10degree CTO 45mmmm -40degree CTO 60mmCmmmm

□□□□	5□-90□□□□□□
□□□□	□□□□1.5□□□□□□□□□□
□□□□	0□10□LUX
□□□□	□□±□□□□□12KV□□□□□±6KV
□□□□	CE□FCC□2□□□□RoHS