

**32** **OCBS-LA09**

**OCBS**

OCBS	
OCBS	650nm
OCBS	200
CPU	32
OCBS	2.5 600 100 UPC / EAN
OCBS	50 @ 60mm 220 @ 200
OCBS	
OCBS	
OCBS	3mil / 5MIL
OCBS	30
OCBS	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code, GS1 DataBar (RSS)
OCBS	±65°; ±60°; ±42°
OCBS	
OCBS	PS2 RS232 USB
OCBS	5V DC ±5
OCBS	85; 100
OCBS	LED
OCBS	ABS + PC
OCBS	156 * 68 * 83 * * *
OCBS	235
OCBS	
OCBS	
OCBS	0°C 45°C
OCBS	-40°C 60°C
OCBS	5-90
OCBS	+/-15kV +/-8KV
OCBS	0 100,000 LUX
OCBS	1.5
OCBS	EN60825-1 1

**OCBS**

