4□□□□□/□□□□□□□□□□

□M / N□OCBP -008□

□□□

□□□□□□□□□□;

200mm / s□8“/ s□□□□□□□□□□□□□□□□;

300m□□□□□□□□214mm□8.4“□OD□□□□□□□;

8MB□□□8MB SRAM□□;

□TSPL / EPL / ZPL / DPL□□□□□□□□□□□□□□□□□;

□□USB2.0□□;

Bartender□□□□□□□& Windows□□□□□□;

□□□□□

□□□	8□/ mm□203 dpi□
□□□□□□	200□□□8□□□/□
□□□□□□	104□□□4.09□□□
□□□□□□	1778□□□70□□□
□□□□	25.4-115mm
□□	□□□USB 2.0 / TF□;
	□□□RS-232 /□□□/ WIFI /□□
□□□□	10□1178□□

□□□	8□/ mm□203dpi□
□□□□	□□□/□□□
□□□□□□	200□□□8□□□/□
□□□□□□	104□□□4.09□□□
□□□□□□	1778□□□70□□□
□□□□	□□□□□□□□□□□□□□□□□□□□□
□□□□	25.4~115□□
□□□□	0.06□0.25□□
□□□□	10~1778mm
□□□□□	□□127□□□5□□□□□□□□□□
□□	ABS□□
□□□□	246□□□□□×223□□□□□×204□□□□□
□□	2.47□□
□□□	32□RISC CPU
□□	8MB□□□8MB SDRAM□Mro SD□□□□□□□□□□□□□□□4 GB

□□	□□□USB 2.0 / TF□;
	□□□RS-232 /□□□/ WIFI /□□
□□	1D□□□Code 39□Code 93□Code 128UCC□Code 128□□A□B□C□
	Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□
	UPC 2□5□□□□□MSI□PLESSEY□POS TNET□□□POS T□GS1 DataBar□Code 11
	2D□□□PDF-417□Maxicode□DataMatrix□QR□□Aztec
□□□□	①RS-232□2400-115200 bps□②□□③WiFi④□□□□
	⑤□□□⑥LCD/ LED□□□□□□□□
□□□□	FCC□CE□CB□CCC
□□□□	□□□□□-10~50°C□14~122℉□□10~90□□□□
	□□□□□-40~60°C□-40~140℉□□10~90□□□□

Aocom®
At your side

OCBP-008

ISO FC CE RoHS

Ocom®

At your side

OCBP-008

ISO FC CE RoHS

Ocom®

At your side

OCBP-008

ISO FC CE RoHS

Ocom®

At your side

OCBP-008

ISO FC CE RoHS

Ocom®
At your side

OCBP-008

ISO FC CE RoHS

Ocom®

At your side

OCBP-008

ISO FC CE RoHS

Ocom®

At your side

OCBP-008

ISO FC CE RoHS