

4 CD

m / n OCBP-012a / b

/  
 200 MHz 32 RISC  
 8 MB SDRAM + 8 MB  
 127 5  
 300 984'  
 203 DPI 300dpi  
 Bartender Label Edition

	OCBP -012A	OCBP -012B.
	8 / mm 203 dpi	12 / mm 300 dpi
	127 mm 5 / s	101.6 mm 4 / s
	108 mm 4.25"	104 mm 4.09"
	1178mm 70	889 35"
	20-112mm 0.78 -4.4"	
	0.06 0.254 mm 2.36 10	
	10 1178 mm 0.39 "70"	10 889 mm 0.39 "35"
	127 mm 5 "OD	
	300 OD 67 mm 1 "40 mm 110 mm 1.6 "4.3"	
	299 mm d x 235 mm w x 198.3 mm h	
	2.55kg.	
	32 RISC CPU	
	8MB	
	8MB SDRAM.	
	SD 4 GB	
	<ul style="list-style-type: none"> <li>•USB2.0</li> <li>•RS-232 • 10/100 Mbps</li> <li>• 802.11 B / G / N</li> </ul>	
	AC 100-240V 1A 50-60Hz	
	DC 24V 2.5A 60W	
	LED 1 1 LED 3	
	8	
	TTF	

□□	1D□□□□□□39□□□□93□□□□128UCC□□□□128□□A□B□C□Codabar□□□□2□ean-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□□□MS□Plessey□POS TNET□□□□POST 2D□□□□PDF-417□Maxicode□DataMatrix□QR□
□□	Bimap□BMP□PCX□□□□256□□□□
□□□□□□□□	0°□90°□180°□270°
□□□□□□	TSPL.
□□	□□□□5□40°C□25□85□□□□ □□□□-40□60°C□10□90□□□□
□□	①Windows□□□□CD□;②□□□□;③USB□;④□□□□;⑤□□□□□□□□□□;⑥□□□□□□□□□□x 2□1.5"□□□□□□x 2;⑦□□□□;⑧media
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□0.06□0.19mm□500000□□; 0.20□0.25mm□200000□□□□
□□□□	□□□□□□□□□□OD□ 214□□□□8.4"□□□□25.4□□□□1"□□□□□□□□□□□□□□□□□□□□□□802.11 B / G / N□□□□□□□□□□RFIDModule□





OCBP-012





OCBP-012





OCBP-012





OCBP-012

