

4GRAM 64G SSD i3 / i5 Linux □□□□□□□□ Pos □□

□□□

1. □□□□□□□□□□ POS □□
2. □□□□□□□□□□□□□□□□□□□□
3. LED / LCD □□□□□□□□
4. MSR □□
5. Wifi □□

□□□

□□	POS 8829
□□□□	□/□□
□□□□□□	ISO Track1 / 2/3 □□□□□□ ; LCD □□□□□ ; LED8; □□□□
□□	□□□□□□
□□□□□	1037U □□ 1.8G
□□□	1037U + ICH8 □□□
□□□□	DDRIII 1066/1333 * 1 2GB □□□ 4GB □
□□□	SATA 2.5 320GB □ 500GB □ SSD 32GB
□□□□□□	15 □□ TFT LCD
□□	□□ 350cd / □ ²
□□□	1024 * 768 □□□□
□□□	5 □□□□□□□□
□□	□□□□ 150; □□□ 140
I / O □□	1 * □□□□
	PS2 □□ * 1; PS2 □□ * 1
	Serial * 3 DB9 □
	□□ * 1 □□ DB25 □□□□
	VGA □□ 15Pin D-sub □□ * 1
	LAN □□ RJ-45 * 1 HDMI * 1 RJ * 11 □□□□□□□□
	USB □□ 2.0 □□ * 6
□□□□ * 12 * □□□□□□□□□□□□ MIC IN * 1	
□□□□	0 □□ 40 □□□□
□□□□	-20 □□ 60 □□□□
□□□□	35W □□□□
□□	FCC A / CE □□ / LVD / CCC
□□□□/□□	440 * 270 * 425mm / 8 KGS
□□□□	Windows XP Professional Embedded □□ WE POS □□ Linux □□□□
□□□□□	110-240V / 50-60HZ □□□□□□□□ DC12 / 5A □□

