

4g pos
M / N POS-Z90

□M / N□POS-Z90□

111

- Android 5.1
- 5.0
- 5600 mAh
- 58
- 500
- 2G / 3G / 4G wifi
- IC
- EMV L1 L2 PCI PBOC
- Thecradle

111

```
applychain[ ]
```

TechnicalSpecification

□□□□	
□□□□	Android 5.1
□□	RAM□1GB
□□□□	FLASH□8GB
□□□	5.0□□
□□□	□□□□□□□□□□ □□
□□	□□□5600□□□3.7□
□□	□□4.0
□□	500□□□□□□
Pos itioning□□	□□Pos itioning□GPS AGPS WLAN
□□□	58mm□□□□□□□30mm□□
□□	□□USB
POS□□	
□□□□□□	□□□□□□□□ □□ISO1788 / 7812□AAMVA□□
IC□□□	□□ISO7816□□
□□□□□□□□	□□ISO / IEC 14443 A& B□Mifare□felica □□□□EMV / PBOC PAYPASS □□
PSAM□	□□□□□□□□□□
□□	□□□□□□□□□□□□ PCI □□ EMV / PBOC3.0 L1□L2□□ EMV / qPBOC3.0 L1□L2□□ □□□□□□□□□□□□□□
□□□□	
□□□□	GSM□WCDMA□TD-SCDMA□FDD-LET□TDD-LTE

無線LAN	GSM850 / 900/1800/1900
	WCDMA2100 / 1900 / HSPA+ / LTE
	TD-SCDMA B34 / B39
	FDD-LTE B1 / B2 / B3 / B4 / B5 / B7 / B8 / B20
	TDD-LTE B38 / B39 / B40 / B41
WLAN	IEEE802.11.b / N / G
本体サイズ	
幅	191mm×80mm×46mm
高さ	650mm
動作温度	-20℃~60℃
保存温度	-40℃~80℃
湿度	10%~90%RH





POS-Z90





POS-Z90





POS-Z90







POS-Z90



► Company



► Certificates



► Payment



► Contact us

