模型 - T2
姓名 5.5英寸电容式触摸屏，
支持电子签名
电池 3.8 伏/ 64 00毫安时
电源适配器输入：100-240V , 50/60赫兹 ,1.5A
输出： 5 V 直流 /2 A
充电器接口 USB C 型
展示
主屏幕 5.5英寸高清触摸屏显示
解决 720*1280 IpS
表现
中央处理器十核MT6797 Tri-Cluste-A72*2A53*8 2.3GHz处理器
内存 3 国标
闪光 16GB闪存
沟通 2G/3G/ 4G
操作系统安卓 8.0
按钮电源按钮、扫描按钮 ,音量按钮
蓝牙蓝牙4.0
无线上网 WIFI 802.11 bgnac
打印机 58mm 热敏收据和标签打印机
纸卷宽度：58mm；直径：≤40mm
扫描器 5兆像素相机解码 , 2D 扫描仪（选配）
近场通信支持ISO/IEC 14443A&B、Mifare、felica卡
SIM卡槽 Sim*2（默认）或Sim*1Sam*1可供选择
扬声器数字音频扬声器
手指 p 林特联邦调查局/STQC 手指 p 林特（选修的）
GPS 或 AGPS 支持GPSAGPS
主数据管理支持
周边配件包裹
配件 USB C 型*1
收费适配器*1
用户手册*1
环境
工作温度 0 到 40 摄氏度
储存温度 - 10 至 60 摄氏度
工作湿度 10%~80%
储存湿度 10%~90%

# POS Terminal with Thermal Label and Receipt Printer

## Model: POS-T2

## Features:

- 5.5-inch Handheld Android POS Terminal
- Deca-core MT6797 Tri-Cluste-A72*2+A53*8 2.3GHz processor
- Built-in high speed 58mm thermal receipt and label printer
- Standard 3GB RAM+16G ROM
- Built-in large volume speaker
- Built-in NFC Module
- 2*SIM card slot
- Support USB type-C fast charging
- Removable 6400mAh large capacity battery
- 1D&2D Bar code reader and fingerprint for option

## Productl Details:

## Productl Specification:

| General | |
|---|---|
| Model | POS-T2 |
| Name | 5.5 inch capacitive touch screen, support the electonic signature |
| Battery | 3.8 V/6400mAh |
| Power adapter | Input: 100-240V, 50/60Hz,1.5A<br>Output: 5V DC /2A |
| Charger interface | USB type C |
| Display | |
| Main screen | 5.5 inch HD touch screen dispaly |
| Resolution | 720*1280 IPS |
| Performance | |
| CPU | Deca-core MT6797 Tri-Cluste-A72*2+A53*8 2.3GHz processor |
| RAM | 3GB |
| Flash | 16GB Flash |
| Communication | 2G/3G/4G |
| Operating system | Android 8.0 |
| Button | Power button, Scan Button, Volume button |
| Bluetooth | Bluetooth 4.0 |
| WIFI | WIFI 802.11 b.g.n.ac |
| Printer | 58mm Thermal Receipt and label Printer |
| Paper roll | Width: 58mm; Diameter: ≤40mm |
| Scanner | 5 Mega-pixel Camera decoding, 2D Scanner (optional) |
| NFC | Support ISO/IEC 14443A&B, Mifare, felica card |
| SIM slot | Sim*2 (default) or Sim*1+Sam*1 for option |
| Speaker | Digital Audio speaker |
| Fingerprint | FBI/STQC Fingerprint (optional) |
| GPS or AGPS | Support GPS+AGPS |
| MDM | Support |
| Peripheral accessories | |
| Accessories | USB type C*1<br>Charging adapter*1<br>User manual*1 |
| Environment | |
| Operating temperature | 0 to 40 degrees centigrade |
| Storage temperature | -10 to 60 degrees centigrade |
| Working humidity | 10%~80% |
| Storage humidity | 10%~90% |

www.ocominc.com