

**Android IOS 58 POS OCPP-M03**

**规格**

|       |                                 |                  |
|-------|---------------------------------|------------------|
| 尺寸    | 105×75×45mm                     |                  |
| 重量    | 134g                            |                  |
| 接口    | USB                             |                  |
| 分辨率   | 48mm                            |                  |
| 打印速度  | ESC / POS 90mm/sec              |                  |
| 打印头   | 90mm/sec                        |                  |
| 打印精度  | 8dots/mm 203DPI                 |                  |
| 打印范围  | 12X24 / 24x24                   |                  |
| 打印列数  | 32 / 16columns                  |                  |
| 打印头间距 | 1.5×3.0 mm / 3.0x3.0mm          |                  |
| 打印精度  | 58.0mm ±0.1mm X40.0             |                  |
| 打印速度  | 0.06/0.08mm                     |                  |
| 接口    | USB/RS-232                      |                  |
| 接口    | USB/RS-232                      |                  |
| 打印速度  | 5K                              |                  |
| 打印速度  | 9V DC/2A                        |                  |
| 打印速度  | DC /1500mA 7.4V; 4-5mm 120-150M |                  |
| 打印速度  |                                 |                  |
| 打印速度  | -10mm 50mm 10mm 90mm            |                  |
| 打印速度  | -20mm 70mm 5mm 95mm             |                  |
| 打印速度  | 30mm ASCII                      |                  |
| 打印速度  | "1234" 6mm                      |                  |
| 打印速度  | 3.5 *1.1mm                      |                  |
| 接口    | OCPP-M05-BB                     | Windows Java     |
|       | OCPP-M05-BB-AI                  | IOS Windows java |
|       | OCPP-M05-UB                     | USB Windows java |
|       | OCPP-M05-U                      | USB Windows java |
|       | OCPP-M05-B                      | Windows Java     |
|       | OCPP-M05-UC                     | USB Windows Java |
|       | OCPP-M05-BC                     | Windows Java     |
|       | OCPP-M05-C                      |                  |



## 58mm Bluetooth Thermal Printer for Andorid or IOS system

OCPP-M03



### Product Picture



## Features

### *Simple but not easy*

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec



Support Windows,Android, or iPhone OS;  
Bluetooth, USB and RS232 communication



Higher print speed 90mm/sec.  
100km TPH Life



Low power consumption and large capacity Lithium battery.



## All-round show





## Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm



## Parameter

|                           |                                     |
|---------------------------|-------------------------------------|
| Overall Dimension (W×D×H) | 105×75×45mm                         |
| Weight                    | 134g                                |
| Color                     | Black                               |
| Effective print width     | 48mm                                |
| Print method              | Thermal line printing               |
| Print commands            | ESC/POS compatible command set      |
| Print speed               | Up to 90mm/sec                      |
| Resolution                | 8 dots/mm(203dpi)                   |
| Print font                | 12x24/ 24x24                        |
| Column capacity           | 32 columns/ 16columns               |
| Character size            | 1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH) |
| Paper dimensions          | 58.0±0.1mm x diameter 40.0mm        |
| Paper thickness           | 0.06 to 0.08mm                      |
| Character set             | Alphanumeric/ Chinese Kanji         |
| Interface                 | USB, RS-232, Bluetooth (optional)   |
| Flash                     | 256KB                               |
| Power Adapter             | 9V DC/2A                            |

## Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

## Shipping and payment

1. EXPRESS: around 3-7 working days to arrive
2. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
3. By sea: depend on which destination port
4. T/T
5. Western Union
6. Escrow
7. L/C



# Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.



□□□□

\*□□□

\*□□□□

\*□□□

\*WinXP Win2000 WinVista Win8-32bit□□□□□

\*Win8-64bit

\*Linux

\*

\*USB Printdemo

\*Printdemo

\*SDK

\*

OCPP-M05-BB USB  
OCPP-M05-BB-Android iOS  
OCPP-M05 USB Android