

58

OCPP - M06

××××××××		105 * 75 * 45mm
		134
		ESC / POS
		48
		90/
		8/ mm203 dpi
		12x24 / 24x24
		32/ 16
		1.5 x 3.0 mm×××/3.0 x 3.0 mm×××
		58.0±0.1mm x40.0mm
		0.060.08
		/
		USBRS-232
		256KB
		9 V CC / 2 A.
		7.4 V DC / 1500 mAH;4-5120-150
		-1050 1090
		-2070 595
posdis		30ASCII
		“1234” 6
		3.5 * 1.1
	CPP-M06-BB	android üSB + COM +
	CPP-M06-BB-AI	android + IOS üSB + COM +
	CPP-M06-B	android üSB + COM +;
	CPP-M06-U	ini android üSB + COM
	CPP-M06-BB-AA	android + IOS üSB + COM +luetoothbattery7 dis pos itivi Android Android +1



www.ocominc.com

CE FCC







www.ocominc.com





3.00

```
OCOMXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX;
```

Global Fortune 500 1 100

12 + 1 pos 24;

30 DOA DOA

pos

4.

T / T LC Western Union Escrow T / T Western Union Escrow Paypal
pos Moneybookers Visa MasterCard Maestro Solo Carte Bleue Pos
tePay CartaSi 4B Euro6000

5.

6.

Eruopean ...

159 2200 500 O2 50

OCOM

· 500 POS Auto-ID

· 1 O2 Star

· 2200 159;

· 11 OEM / ODM

· POS

· pos ta res

· ISO FCC CE Soncap POA BIS

· 12 + 1

· “ ”

·