

# 58mm 80 Pin Thermal Receipt Printer [OCP-M03]

## Features

Compact size  
 Easy to use  
 Quiet operation  
 58mm receipt width

## Specifications

Windows, iOS, JAVA compatible  
 USB, RS232C interface  
 Receipt width: 58mm  
 Receipt length: 90mm / 100mm  
 Receipt speed: 100KM/h  
 Quiet operation

## Dimensions

Dimensions (mm) (W x H x D)	105 x 75 x 45
Weight	134g
Receipt width	58mm
Receipt length	90mm / 100mm
Receipt speed	ESC / POS compatible
Receipt thickness	0.075mm / 0.08mm
Receipt weight	1.5 x 3.0mm (width) x 3.0 x 3.0mm (height)
Receipt length	58.0mm ± 0.1mm x 40.0
Receipt width	0.06mm / 0.08mm
Receipt length	0.06mm / 0.08mm
Interface	USB, RS-232C
Memory	256KB
Power supply	DC 9V / 2A
Power consumption	DC / 1500mAh 7.4V; 4-5 hours (typical) 120-150mAh
Operating temperature	0°C to 40°C
Operating humidity	10% to 90%

□□□□	□□□-20Celsius□70CelsiusHumidity□5□□95□□	
□□□□	□□□□□□□□□□□□□□30□ASCII□□□□	
□□	□□□□□□□“1234”□□□□□□□□6□□□□□□	
□□□□□□□□	3.5 *1.1□□	
□□□□	P / N	□□
	OCPP-M03-BB	□□□□□□□□□□supprot□Android
	OCPP-M03-BB-I	□□□□□□□□□□supprot Android□iOS
	OCPP-M03-UB	□□Barrery USB□□□□
	OCPP-M03-U	USB□□□□□□BT□□□□
	OCPP-M03-B	Bluetooth□□□□□□□□
	OCPP-M03-UC	USB□□□□□□□□□□
	OCPP-M03-BC	□□□□□□□□□□
	OCPP-M03-C	□□□□

