

# 80 ATM

OCKP-8002

□□□

160mm / s□□□□□□

□□80□□□□□□

□□□□□□

□□□□□□□□□□

□□□□□□

□□NV□□□□□□

□□□□□□□□□□

□□□□□□100km

□□□

□□□□	□□□
□□□□	160□□/□
□□□□	Φ80□□
□□□	576□□/□
□□	0.06□0.08□□
□□	USB + RS232
□□	GB18030□□□□□□/□□□□□□□□□□
□□□□	ANK□□□A□1.5×3.0mm□12×24□□□□□B□1.1×2.1mm□9×17□□
□□□□	UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□/ CODE39 / ITF / CODABAR / CODE93 / □□128 2D□QRCode / PDF417
□□□□□□	32K□□
NV□□	64K□□
□□□□□□	DC24V / 2.5A
□□□□□□□□	□□24V / 1A
□□	0.37□□
□□□□	132.2×125.7×88.11mm□□×□×□□
□□□□	□□□0□45□□□□10□80□□
□□□□	□□□-10□60°C□□□□10□80□□
□□□□□□	100□□



OCKP-8002





OCKP-8002





OCKP-8002







OCKP-8002









OCKP-8002







OCKP-8002





OCKP-8002

