

80
OCPP-809

	576dots /ling&NBSP; 512dots /;	
	24x2418030 ANK ;	
	A12 * 241.5* 3.0mm; B9 * 17dots1.1* 2.1mm 24 * 243.0* 3.0mm	
	JUPC-A / UPC-E / JAN13EAN13/ JAN8EAN8/ CODABAR / ITF / CODE39 / CODE93 / CODE128QR	
	250/300	
	USBUSB + USB + LANUSB + + LAN+ USB+ USB + LAN	
	EPSON ESC / POS	
	WIN9X /WIN XP / WIN2000 / Win2003/ WIN Vista/WIN 7 /WIN 8 / win8.1 / LinuxESPONSDK Android	
	79.5±0.572	
	83	
	0.06-0.08mm	
	100km	
	DC24V / 2.5A	
	0-45	
	10-80	
	190 * 145 * 145MM	
	1.60	
	P / N	
	OCPP-809-U	USB
	OCPP-809-UR	USB +
	OCPP-809-UL	USB + LAN
	OCPP-809-L	USB + + LAN
	OCPP-809-W	+ USB
	OCPP-809-BUL	+ USB + LAN
	OCPP-809-U0	USB
	OCPP-809-UR0	USB +
	OCPP-809-UL0	USB + LAN
	OCPP-809-URL0	USB + + LAN
	OCPP-809-W0	+ USB
	OCPP-809-BUL0	+ USB + LAN

□□□□□



□□□□□□□

