

80mm x 103mm x 45mm
OCPP-M082

Specifications

| | |
|-----------------------|--|
| Dimensions (WxDxH) | 98x103x45mm |
| Weight | 280g |
| Material | ABS |
| Resolution | 72DPI |
| Interface | USB |
| OS Support | ESC / POS |
| Print Speed | 90mm / min |
| Print Density | 8dots / mm @ 203DPI |
| Print Format | 12x24 / 24x24mm |
| Print Columns | 48 / 24 columns |
| Print Size | 1.5x3.0mm x 3.0x3.0mm |
| Print Accuracy | 80.0um ± 0.1mm x 30.0 |
| Print Resolution | 0.06mm x 0.08mm |
| Print Language | ASCII / UTF-8 |
| Interface | USB / RS-232 |
| Memory | 256KB |
| Power Supply | DC 9V / 2A |
| Power Consumption | DC / 2000mAh @ 7.4V; 4-5W (idle) / 120-150mW (print) |
| Operating Temperature | 0-40°C |
| Storage Temperature | -10 to 50°C (10 to 90°F) |
| Humidity | 20-80% RH (5-95%) |
| Print Language | ASCII (30 characters) |
| Print Content | Printable area: 12x24mm (6 dots) |
| Dimensions | 3.5 * 1.1 inch |

Notes



Additional Info

For more information, visit [www.ocpp.com](#)

OCPP
SDK