

80mm Pos □□□□/□□□□□□□□

(□□: OCBP-005)

□□:

□□□□□□	OCBP-005
□□	203 DPI (8 □/□□)
□□□□	□□□□
□□□□□□	□□□□
□□□□□□	□□□□
□□□□	□□□□□□
□□□□	127□□/□ (□□);50.8mm/□ (□□)
□□□□	16□□□82□□
□□	□□□□: □□□□□□□□□□□□ □□□□: □□:25 □□:□□:80 □□
□□□□	□□0□□ 8;□□□□□□□□□□
□□ & □□	1-10 □□□□□□□□;0□, 90 □, 180 □, 270 □, 360 □□□
□□□□□□	□□ & □□
□□□□	2MB □□ ROM, 2MB □ DRAM
□□	□□ PCX, BMP □□□□□□□□□□□□, DRAM
□□	CODE128, EAN128, Code39, Code93, EAN13, EAN13 + 2, EAN13 + 5, EAN8, EAN8 + 2, EAN8 + 5, CODABAR, POSTNET, upc A, UPCA + 2, UPCA + 5, upc E, UPCE + 2, UPCE + 5, CPOST, MSI, MSIC, □□□, ITF14, EAN14, PDF417, QR □, DATMATRIX
□□	usb + RS232 + □□□□□□ usb
□□	□□: 24VDC, 2.5A
□□	□□□□: 5 ° c □45□□□ □□□□: -40 □□□□55□□□ □□□□: 20% ~ 80%, □□□□, □□□□ □□□□: < = 93% (40 °C), □□□□, □□□□
□□	□□: D220mm * H148mm * W150mm

□□□□□□□□:



□□□□:

□□□□□□□□□□, □?□□□□□□□

[□□](#)
[OCBP-005 □□□□□□□□](#)