

# 80

## OCPP-80E

### 

- 3.
- 4.
5. 100M
6. 256kb NV Logo 2M
7. OPOS
- 8.

### 

	230mm/s-----260mm/s
	79.5±0.5mm
	72mm
	Φ80mm
	0.06-0.08mm
	576/512
	3.75mm
	ESC/POS
	/36P/25P+USB /+USB+
	ANK:FontA:1.5*3.0mm/ FontB:1.1*2.1mm
	UPC-A/UPC-E/JA/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128/QRcode
	PC347/Standard Europe/Katakana/PC850/Multilingual/PC860/Portuguese/PC863/Canadian-French/PC865/Nordic/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/Cyrillic#2/PC852/Latin2/PC858/IranII/Latvian/Arabic/PT151/1251
	100
	100
	2MB
NV Flash	256KB
	AC110V/220V 50~60Hz
	DC 24V/2.5A
	DC 24V/2.5A
	DC 24V/1A
	0~45 10~80
	-10~60°C 10~90°C
	1.25 190×145×143×××

x x x x

x

x

x

x

x

x

x

x