

80MM

OCPP -80Y



USB+LAN+USB+RS232+URL

256KB NV2M

	160
	79.5±0.5
	Φ80mm
	0.06-0.08mm
	576/ line512
	3.75mm
	ESC / POS
	USB+LAN+USB+RS232+USB+RS232+LAN
	100
	100
	2048Kbytes
NV Flash	256K
	AC110V / 240V5060HZ
	DC 24V / 2.5A

تغذیه	DC 24V / 1A
سرعت چاپ	۰~۴۵ خط در ثانیه / ۱۰~۸۰ میلی متر در ثانیه
حداکثر عرض چاپ	۰-۴۵ میلی متر / ۱۰-۸۰ میلی متر
دما	۱۰~۶۰°C; رطوبت ۱۰~۹۰٪
فونت	ANK FontA 1.5 * 3.0mm / FontB 1.1 * 2.1mm
کدهای چاپ	UPC-A / UPC-E / JAN EAN13 / JAN8 EAN8 / CODE39 / ITF / CODE93 / CODE128 QR PDF 417
زبان	PC347, PC850, PC860, PC863, PC865, WPC1252, PC866, PC852, PC858, PT151, 1251
وزن	۱.۲۵Kg













□□□□□□□□



□□□□□

▶ Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant



□□□□

□□80□□□□POS□□□□