

POS

ECD-410D

□□

45□□□□□□□□8□□□□□□□□  
□□□□□□□□□□□□□□  
9V□24V□□□  
□□□□□□□□  
□□3 positions

□□

□□	□□□0.8□□SPCC□□□□□□□□□□ □□□1.0mm SECC□□□□□□
□□□□	□□positions□□□85/84/84/85 mm □□position□□□68/67/67/67/68 mm □□□193□□;□□□59□□
□□	8□□□□Pos ition□□□82;□□□57;□□□46
□□	3□□
□□	12V 24V□□□
□□	□□□□□□□□□□
□□	RJ11 / RJ12
□□	□□□
□□	6.5□□□□□□7.0□□□□□□
□□□□	410□□□x 415□□□x 100□□□□□□□□10□□□

□□□□



# ECD-410D



[www.ocominc.com](http://www.ocominc.com)





[www.ocominc.com](http://www.ocominc.com)





## Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

