

□□□□□□□□□□□□□□□□

**M / N OCBP -007-U**

**□□□1**

- 
- 32 RISC CPU
- 8MB SDRAM □4MB □□
- 
- 203 dpi □□□
- 102mm □4'' □/ s □□□□□
- 108mm □□□□
- 20-112mm □0.78"-4.4" □□□ □edia □□

**2.Parameters**

□□	
□□□	8 / mm □203DPI
□□□□	□□□□
□□□□□□	102□□□4'' □/ S.
□□□□□□	108□□□4.25□□□
□□□□□□	2286□□□90□□□
□□□□	□□□□□□□□□□□□□□□□
□□□□	20-112mm □0.78"-4.4" □
□□□□	0.06 □0.16 □□□□2.36 □6.3mil □
□□□□	10 □2286 □□□0.4 " " □90 " " □
□□□□□□	□□127□□□5□□□□□□□□
□□	□□□□
□□□□	240□□□w ^ □×211□□□H □×166□□ □d □
□□	2.15□□
□□□	32 RISC CPU
□□	4MB □□8MB SDRAM □□□□□□□□SD □□□□□□4 GB
□□	USB 2.0
□□□□	8□□□□□□□□□□Windows □□□□□□□□□□
□□	1D □□□□Code 39 □Code 93 □Code 128UCC □Code 128 subsets A □B □C □Codabar □Interleaved 2 of 5 □EAN-8 □EAN-13 □EAN-128 □UPC-A □UPC-E □EAN □UPC 2 □ 5 □□□□□□□□MSI □PLESSEY □POS TNET □□□□POS T. □□□□□□PDF-417 □Maxicode □DataMatrix □QR □
□□□□□□□□	0° □90° □180° □270°
□□□□	□□□5~40°C □25~85□□□□□□□□-40~60°C □10~90□□□□

**3.Pictures**




Product Picture



Features

32-bit RISC CPU, 8MB SDRAM, 4MB Flash;



20-108mm printing width adjustable;

Support PDF417, QR CODE, DOTMATRIX;



Support USB, Serial, LAN(OPTION);

All-round show



Application Area



Parameter

Resolution	8 dots/mm(20DPI)
Printing method	Direct Thermal
Max print speed	100 mm/47.24"
Max print width	108 mm (4.25")
Max print length	2286 mm (90")
Media type	Continuous, gap, notch mark, Non-Fast and punched hole
Media width	20-108mm (0.78"-4.3")
Media thickness	0.08-0.16mm (3.5-6.3mil)
Label length	10-2.286mm (4"-90")
Label roll capacity	127 mm (5") OD (includes unwind)
Structure	Single or dual platen
Physical dimension	240 mm (L) x 211 mm (W) x 166 mm (D)
Weight	2.1kg
Processor	32-bit RISC CPU
Memory	4MB Flash Memory, 8MB SDRAM, SD card reader for Flash memory expansion, 32K x 4 GB
Interface	USB 2.0
Internal ports	8-pin serial, Serial ports, Windows ports are also available from 4-pin area.
Barcode	1D bar code: Code 39, Code 93, Code 128, UCC, Code 128 subsets A, B, C, Code 128 extended (UPC-E, EAN-8, EAN-13, EAN-18, UPCA, UPEC-E, EAN-12 and UPCA-20), 1D sign add-on, MSI, PLESSEY, POSTNET, China POST
Font and barcode extension	2D bar code: PDF417, Microcode, DataMatrix, QR code
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing. Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

Production Line



**4.FAQ**

1

2

t / twestern uionpaypalaliexpress  
http://www.aliexpress.com/store/403448?tracelog = minisite\_CI

3

OCOM

500100

12 + 124

30DOA DOA

4

T / TLCWestern UnionEscrowT / TWestern UnionEscrowPaypal  
.EscrowAlipay.comMoneybookersVisaMasterCard  
MaestroSoloCarte BleuePos tePayCartaSi4BEuro6000

**5.**

OCOM Technologies Ltd.TUVPOSAuto-ID OCOM5001

OCOMPOSPOSPOSPOS  
CEFCC

OCOM“”OEM / ODM