

80MM WIFI

M / N OCPP-80F

1. 300mm / s
2. 2048K
3. 1D 2D
- 4.
- 5.;
- 6.
7. 80MM 58MM

	72mm
	576/512/8/ mm 203dpi
	300mm /
	USB + COM + LAN USB USB + LAN + WIFI USB + BT + WIFI USB + BT
	3.75mm
	FontA-48Lines / FontB-64Lines / 24
	GB18030/
	ANK A 1.5x3.0mm 12x24 FontB 1.1x2.1mm 9x17/3.0x3.0mm 24x24
	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 / WestEurope / Greek / Hebrew / EastEurope / Iran / WPC1252 / PC866 / PC852 / PC858 / IranII / Latvian / Arabic / PT151,1251 / PC737 / WPC / 1257 / ThaiVietnam / PC864 / PC1001 / PC1001/PT151,1251/WPC1257/PC864/ /
	1D UPC-A / UPC-E / JAN13/EAN13/ JAN8/EAN8/ CODE39 / ITF / CODABAR / CODE93 / CODE128 QR CODE
	79.5±0.5mm
	≤80mm
	Feed Clameshell Feed
	ESC / POS
	AC 110V / 220V 50/60Hz DC 24V / 2.5A

電源	DC 24V / 1A
メモリ	2048KB
NVメモリ	256KB
重量	1.2KG
寸法	186 * 145 * 135
動作温度	5~45°C
保存温度	-10~50°C
湿度	10~90% Nodew
動作速度	100KM/LE.12.5
容量	1000,000
対応OS	Android、IOS、Linux、Win2000、Win2003、WinXP、Win7、Win8、Win8.1