

OCBS-W229

OCBS-W229

OCBS-W229
 433MHZ;
 300;
 60/35;
 RS-232C; USB2.0;
 2.5/175;
 ;

OCBS-W229

OCBS-W229	97.3mmLx60.3mmWx181mmH		
OCBS-W229	175		
OCBS-W229	1.8		
OCBS-W229	5 + / -10VDC 350 mA		
OCBS-W229	528 nm LED; 630 LED		
OCBS-W229	34° V X 46° ×		
OCBS-W229	360° ±65° ±60°		
OCBS-W229	OCBS-W229	TD3000	
	OCBS-W229		
	OCBS-W229	1.2-8.0	3.0 20.5
	OCBS-W229	1.2-12.0	3.030.5
	OCBS-W229	2.0-6.0	5.0-15.5
OCBS-W229	OCBS-W229	2.1-6.0	5.2-15.5
	OCBS-W229		
	OCBS-W229	UPC / EAN 39 39 ASCII 39 RSS UCC / EAN 128 128 ASCII 93 NW1 2 5 Codell IATA Bookland EAN 32	
	OCBS-W229	PDF417 MicroPDF417	
	OCBS-W229	Postnet	
OCBS-W229	OCBS-W229	MaxiCode DataMatrix ECC 200 QR	
	OCBS-W229	25	
	OCBS-W229	2 5	
OCBS-W229	RS-232C ICL; USB IBM SurePOS Macintosh		
OCBS-W229	0.30x640x480xV		
OCBS-W229	JPEG Tiff		
OCBS-W229	3 35		
OCBS-W229	USB 1.1 12 Megabits/second RS232 115 kb		
OCBS-W229	USB 0.2 100 kb JPEG		
OCBS-W229	433MHz		
OCBS-W229	800		10M/100M
OCBS-W229	64		/
OCBS-W229	USB-HID USB-COM		/
OCBS-W229	1.2K 38.4K 9.6kbit /		/
OCBS-W229	8MB		
OCBS-W229	435		
OCBS-W229	525		
OCBS-W229	66		
OCBS-W229	2400mAH		
OCBS-W229	> = 4		
OCBS-W229			
OCBS-W229	5VDC ±10VDC		

OCBS-W229-R-B	433MHz
OCBS-W229-R-W	67
OCBS-W229-B-B	14° 122°F / -10° 50°C
OCBS-W229-B-W	-40° 158°F / -40° 70°C
OCBS-W229-B-B	5 95
OCBS-W229-B-W	2000
OCBS-W229-B-B	
OCBS-W229-B-W	
OCBS-W229-R-B	433MHz
OCBS-W229-R-W	433MHz
OCBS-W229-B-B	
OCBS-W229-B-W	

OCBS-W229-R-B

OCBS-W229-R-W

OCBS-W229-B-B

OCBS-W229-B-W

OCBS-W229-R-B