

XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXX **USB + LAN + SERIAL** **OCBP-005**

XXX

XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXX;

XXXXXXXXXX;

XXXXXXXXXXXX;

XXXXXXXXXXXX;

□BMP□PCX□BAC□XXXX;

XXXXXXXX□USB□LAN□XX;

XXXXXXXX□PDF417□QR□DOTMATRIX;

XXX

XXXXXXXXXXXXXXXXXXXX

XXXX	OCBP-005
XX	203 dpi□8□/□
XXXX	XX
XXXXXXXX	XXXX
XXXX	XX
XXXX	XX
XXXX	127□/□□□□□□ 50.8□/□□□
XXXX	16□□82□
XX	XXXXXXXXXXXXXXXXXXXX
	XXXXXXXX□25□;□□80□
XXXX	□□FONT 0 8□□□□□□□□
XXXXXXXX;□□□;□□□;□□□	1-10□□□□□□□□; 0°□90°□180°□270°□360°
XXXXXXXX	□□&□□;□□□;□□□;□□□
XX	2MB FLASH ROM□2 MB DRAM
XX	□□PCX□BMP□□□□□□□□Flash□□□□DRAM
	CODE128□EAN 128□ITF□39□□CODE93□EAN13□EAN13 2□5
XX	EAN13□EAN8□EAN8 2□5□EAN8□□□□□POSTNET□UPC-A□UPCA 2□UPCA
	5□UPC-E□UPCE 2□UPCE 5□CPost□
	□□MSIC□PLESSEY□ITF14□EAN14□PDF417□QR□□DATMATRIX
XX	USB + RS232 + LAN□USB
XX	□□□24VDC□2.5A
	□□□□5°C□45°C
XX	□□□□-40°C□55°C
	□□□□□20□□80□□□□□□□□□□
	□□□□□□□;□□□;□□□;□□□; LT□ = 93□□40°C□□□□□□□□□□
XX	□□□D220mm H148mm * W150mm *

XX XXX

XXXXXXXXXXXXXXXXXXXX

