

QR RS232

OCBS -L009



□□□

200scan / sec□□□□□□□□□□;

□□□□□□□□;

□□KBW□RS232□USB;

□□□□□□□□□□□□;

□□□□□□□□□□

□□□

□□□□	
□□□□	650nm□□
□□□□	□□200□□□
□□□□□□	32□
□□□□	2.5~600mm□100□UPC / EAN□
□□□□	50mm @ 60mm□220mm @ 200mm
□□□□□□□□	□□
□□□□	□□
□□□□	3mil□□□□□□□□ / 5mil□□□□□□□□
□□□□□□□□□□	30□□□□□□□□□□
□□□□□□	UPC / EAN□UPC / EAN□Supplemental□UCC / EAN 128□Code 39□Code 39 Full ASCII□Trioptic Code 39□Code 128□Code 128 Full ASCII□Coda bar□Interleaved 2 of 5□Discrete 2 of 5□Code 93 □MSI□Code 11□RSS □□□□□□2 of 5□MSI / Plessey□□□□□ / Plessey□UCC / EAN 128□□□□□□□□GS1□□□□ □RSS□□□□
□□□□	±65°□□□□□□; ±60°□□□□□□; ±42°□□□□□□
□□□□	
□□□□□□□□	PS2□RS232□USB
□□□□	5V DC±5□
□□□□	85 mA□□□□□□; 100□□□□□□
□□□□	□□□□□□LED
□□	ABS + PC

重量	156 * 68 * 83 mm
尺寸	156 * 68 * 83 mm
重量	235g
颜色	黑色
工作温度	0°C~45°C
存储温度	-40°C~60°C
湿度	5%-90%
静电放电	±15KV 接触 ±8KV 空气
照度	0~100,000 LUX
扫描距离	1.5m
符合标准	EN60825-1 Class 1



OCBS-L009





OCBS-L009





OCBS-L009





3. 3

OCOM

500 100

12 + 1 24

30 DOA DOA

4. 4

T / T LC Western Union Escrow T / T Western Union Escrow Paypal Escrow Alipay.com Moneybookers Visa MasterCard Maestro Solo Carte Bleue Pos tePay CartaSi 4B Euro6000

5. 5

6. 6

Eruopean

133 1300 O2 500 50

OCOM

500 POS

O2 Star .....

1500 133

9 OEM / ODM

POS

FCC CE Soncap POA BIS

12 + 1

"