

OCBS-2008

OCBS-2008

OCBS-2008

OCBS-2008;
OCBS-2008;
OCBS-2008;
OCBS-2008;
4mil;
OCBS-2008;
SDK / API;
OCBS-2008;
OCBS-2008

OCBS-2008

Table with 2 columns: Parameter and Value. Rows include: LED, CMOS, 640 * 480 256, 13mil UPC40, 50, 20, ≥4mil, 1D (UPC-A, UPC-E, etc.), 2D (PDF417, QR Code, etc.), 39, 10MIL, 25, 250, UPC / EAN, 13mil, 20, 320, 7.5mil, 63, 150, PDF417, 6.6mil, 62, 145, ±45°@ 0°, ±30°@ 0°, ±45°@ 0°, USB, USB COM, 3.3V, 5V DC, 2.0, 400, 2.5, 450, DC, 5.5V 1A, LED CLASS, Class I, EMC, FCC part15, IEC60825-1, EN55022 Class B.

□□□□	
□□□□	-20□□□□60□□□□-4□□□□144□□□□
□□□□	-30□□□□70□□□□-22□□□□158□□□□
□□	5□ - 95□□□□□□
□□□	1.5□□5.0□□□□□□□□□□
IP□	IP54
□□	□□□□□□□□□□
□□	
□□	156 * 68 * 83□□
□□	195□□□□□□□□
□□□□	48 * 36 * 47CM□20□□□□□□13.5□□□
□□□□	48 * 39 * 52CM□30□□□□□□15□□□