

80 POS OCPP-88A-URL
OCPP-88A

;
 300/;
 ;
 ;
 USB + USB + LAN + LAN; Wifi + USB + USB + LAN
 ;
 ;
 ;
 SDK Android;
 ;
 EPSON ESC / POS

OCPP-88A	OCPP-88A
Resolution	576dots / 512dots ; 24x24 18030 ANK;
Dimensions	12 * 24dots 1.5W * 3.0H ; 9 * 17dots 1.1 * 2.1mm 24 * 24dots 3.0W * 3.0H
Barcode	JUPC-A / UPC-E / JAN13 EAN13 / JAN8 EAN8 / CODABAR / ITF / CODE39 / CODE93 / CODE128 QR
Weight	250 / 300mm /
Connectivity	USB + USB + LAN + LAN + USB + USB + LAN
Software	EPSON ESC / POS
OS	Win9X / XP / WIN2000 / Win2003 / VISTA / Win 7 / 8 / win8.1 / Linux ESPON SDK Android
Power	79.5 ± 0.5 W
Temperature	83
Thickness	0.06-0.08mm
Material	
Input	
Output	DC24V / 2.5A
Current	0-45
Frequency	10-80
Size	190 * 145 * 145 MM
Weight	1.60

□□□□	P / N	□□
	OCPP-88A-U	USB□□□□□□□□
	OCPP-88A-UR	USB + □□□□□□□□
	OCPP-88A-UL	USB + LAN□□□□□□□□
	OCPP-88A-URL	USB + □□+ LAN□□□□□□□□
	OCPP-88A-W	□□+ USB□□□□□□□□
	OCPP-88A-BUL	□□+ USB + LAN□□□□□□□□
	OCPP-88A-U0	USB□□□□□□□□
	OCPP-88A-UR0	USB + □□□□□□□□
	OCPP-88A-UL0	USB + LAN□□□□□□□□
	OCPP-88A-URL0	USB + □□+ Lan□□□□□□□□
	OCPP-88A-W0	□□+ USB□□□□□□□□
	OCPP-88A-BUL0	□□+ USB + LAN□□□□□□