

RFID PDA

No.:OCBS-D8000

Feature

Android5.1;  
 2G 16G ROM TF 32 GB;  
 ARM Cortex-A53 64 1.3GHz;  
 4G LTE 3G WCDMA;  
 GPS A-GPS;  
 800 LED;  
 SIM PSAM SD TF;  
 3.7V 4000mAh;  
 4.0 QVGA;  
 IP65;  
 6 1.5

Spec

Screen	
Size	152mm L x 77mm W x 29mm H
Weight	<500g
Display	4.0" QVGA TFT-LCD 65mm 480x800 QVGA LED
Storage	SIM PSAM SD TF
Ports	USB2.0 RS-232
Connectivity	
Battery	3.7V 4000mAh
Power	8W
Dimensions	29pcs
Processor	
Chipset	ARM Cortex-A53 64 1.3GHz
RAM	2G
ROM	16G NAND Micro SD / TF 32G
OS	
Standards	IEEE802.11b / g
FDD-LTE	1920MHZ-1980MHZ; 2110MHZ-2170MHZ 1710MHZ-1785MHZ; 1805MHZ-1880MHZ 2496MHZ-2690MHZ; 2496MHZ-2690MHZ
WCDMA / GSM	WCDMA 1850MHZ-1910MHZ; 1930MHZ-1990MHZ 880MHZ-915MHZ; 925MHz-960MHZ GSM 850MHZ 824MHZ-849MHZ; 869MHZ-894MHZ 900MHZ 880MHZ-915MHZ; 925MHz-960MHZ 1800MHZ 1710MHZ-1785MHZ; 1805MHZ-1880MHZ 1900MHZ 1850MHZ-1910MHZ; 1930MHZ-1990MHZ
Camera	2.0 + EDR 5-10
Temperature	
Operating Temp	-20°C 50°C

温度	-25°C~70°C
湿度	5%RH - 95%RH
重量	6g
尺寸	1000μ / 0.5M
防护等级	IP65
操作系统	Android5.1
SDK	Android
编程语言	JAVA
接口	
摄像头	SE655
分辨率	5MIL
照度	0ft.candles-10000ft.candles
帧率	50 /s
视角	53°±3°
编码	UPC / EAN / EAN / Bookland / 128 / 39 / 93 / 11 / 5 / 2 / 5 / 2 / GS1 / DataBar
品牌	Mingde966 / 955 / HoneywellN4313
分辨率	4MIL
照度	10000ft.candles / 107640
精度	104±12 / Bothway
精度	47°±35° / 35°±3°
编码	UPC / EAN / 128 / 39 / CODE93 / Code11 / 5 / 2 / 5 / 2 / RSS
接口	
CMOS	3096 / N3680
分辨率	752×480
照度	9000ft.candles / 96900
波长	655nm±10nm
编码	PDF417 / MicroPDF417 / RSS / TLC-39 / QR / QR / MAXICODE; / POSTNET / JapanPostal / KIX3
RFID	
LF	125K; ISO11784 / ISO11785
HF	13.56MHz; ISO14443A / B
光源	800nm LED
接口	A-GPS

