

□□□□□□□□□□□□□□□□  
□□□□□□□-W230□

□□□□	
□□	95x65x155mm
□□	ABS + PC
□□	160□

□□□□	
□□□□	617□□LED
□□□□	625□□LED
□□□□	39°□H□×25°□V□
□□□□	0 - 360°
□□	±65°
□□	±60°
□□□□□	□□25□
1D	UPC / EAN□UPC / EAN□□□□BooklandEAN□ISSN□UCC□□□□□□□□Code128□GS1-128□ISBT 128□□39□□39□FullASCII□Trioptic 39□□32□□93□□Code11□□□2 5□□□2 5□□□2of 5□□□□□□□□5□□2□GS1 DataBarvariants□□□35□ISBT Concat□
2D	PDF417□MicroPDF417□□□□□□TLC-39□□□□□□MAXICODE□QR□□MicroQR□□□□□□
□□	USB
□□□□	□□□1□□□□□□□□300m□□□□□□
□□□□	-10°C - 45°C
□□□□	-20°C - 65°C
□□□□	5□-85□
□□□□	5□-95□
□□□	□□□□□1.8□□□□□□□□□
□□□□	DC 5V□350mA
Lumination	□□□3.000 LUX□□;□□□□86000LUX□□
EMC	EN50081□PAR1□□
FCC	EN50082□PAR1□□
IP□□	IP42
□□□□□□	
□□□□*	□□□□□□□□
	HD□□□□□
□□□□	□□□□
39□	5.0□
100□UPCA	13.0□
39□	20.0□
PDF 417	6.8□
□□□□	10.0□
QR□	20.0□
□□□1D□39	
□□□□□□□□	

