

LA09

Table 1

Wavelength	650nm
Power	200mW
Beam diameter	32
Spot size	2.5mm @ 600mm / 100mm UPC / EAN
Beam divergence	50mrad @ 60mm / 220mrad @ 200mm
Beam quality	1
Beam stability	100%
Beam diameter	3mil / 5mil
Beam diameter	30mil
Beam diameter	UPC / EAN / UPC / EAN / UCC / EAN 128 / 39 / 39 / ASCII / Trioptic 39 / 128 / 128 / ASCII / 5 / 2 / 5 / 93 / 11 / RSS / 5 / 2 / MSI / Plessey / UK / Plessey / UCC / EAN 128 / GS1 / DataBar / RSS
Temperature	±65°C; ±60°C; ±42°C
Interface	PS2 / RS232 / USB
Voltage	5V DC ±5%
Current	85mA; 100mA
Light source	LED
Material	ABS + PC
Weight	156 * 68 * 83mm L * W * H
Dimensions	235mm
Dimensions	100mm
Operating temperature	0°C to 45°C
Storage temperature	-40°C to 60°C
Humidity	5% - 90%
ESD	±15kV / ±8kV
Illuminance	0 to 10 LUX
Beam diameter	1.5mm
Standard	EN60825-1

Table 2

