

□□□□**433MHz**□□□□□□□□□□  
□□□□**OCBS-W800**□

□□□□

□□CHARACTERSTICS	
□□□	□□□□□□□□VLD□@ 650□□
□□□□□ □	168□□*72□□*93□□□W * H * D□
□□□□□□	130□□*45□□*129□□□W * H * D□
□□□	ABS + TPR /□□□
□□□	370□
□□□□□	□□□;□□□□□□□□
□□□□	LED□□□□□□
□□□□	□□□□□□□□
□□CHARACTERSTICS	
□□□□□	60□□@30□□□□□□□□□□□□ 98□□@ 100□□□□□□□□□□□□
□□□□□□□□	10-450mm□□□□0.9□□0.25□
□□□□□	150□/□
□□□□□	0.10-0.825mm
□□□□	1 /□500□□
□□□□□	UPC / EAN□□UPC / EAN□□□□UCC / EAN128□39□□39□□ASCII□Trioptic 39□□128 □□128□□ASCII□□□□□□5□□2□□□2 5□□□93□□□□□□□11□RSS□□□□5□MSI / Plessey□□UK / Plessey□□□□UCC / EAN 128□□□□□□□GS1□DataBar□□RSS□□□□□□□2
□□□	3.7V / 750mAh□□□□□□
□□□□□	3.0□□
□□□□□	30□□
□□□□□	95□□□□□□□; 25□□□□□□□
□□□	□□□60°;□□45°
□□□□□	433MHz□
□□□□□	200□□□□□□□□□
□□□□□	USB
□□□□CHARACTERSTICS	
□□□	-10degree CTO 45□□□ □□□□□-40degree CTO 60□C□□□□□
□□□□□	5□-90□□□□□□□□
□□□□□	□□□□1.5□□□□□□□□□□
□□□□□	0□10□LUX
□□□□□	□□±□□□□□12KV□□□□□□±6KV
□□□□□	CE□FCC□2□□□□□RoHS

□□□□□□□



□□□□

Information 

  
  
  
