

□□□□□□□□□□□□□□□□

□□□□□□-W230□

□□□

□□□□	617□□LED		
□□□□	625□□LED		
□□□□	39°□H□×25°□V□		
□□□□	0 - 360°		
□□	±65°		
□□	±60°		
□□□□□□	□□25□		
1D	UPC / EAN□□UPC / EAN□□□□□□BooklandEAN□□ISSN□□UCC□□□□□□□□□□Code128□□GS1-128□□ISBT 128 □□39□□39□□ASCII□□Trioptic 39□□32□□93□□Code11□□□□□□2 5□□□2 5□□□2of 5□□□□□□□□□□5□□2□□GS1 □□Barvariants□□□3 5□□□□□□□□Concat□		
2D	PDF417□□MicroPDF417□□□□□□□□TLC-39□□□□□□□□MAXICODE□□QR□□MicroQR□□□□□□□□		
□□	USB		
□□□□	□□□□1□□□□□□□□□□□□300m□□□□□□□□		
□□□□	-10□□□□ - 45□□□□		
□□□□	-20□□□□ - 65□□□□		
□□□□	5□-85□		
□□□□	5□-95□		
□□□□	□□□□□□□□1.8□□□□□□□□□□□□		
□□□□	DC 5V□□350mA		
Lumination	□□□□3.000 LUX□□□□;□□□□□□□□86000LUX□□□□		
EMC	EN50081□□PAR1□□□□		
FCC	EN50082□□PAR1□□□□		
IP□□	IP42		
□□□□			
□□□□*	□□□□□□□□□□		
	HD□□□□□□		
□□□□	□□□□□□		
39□	5.0□	5□□	90□□
100□UPCA	13.0□	8□□	200□□
39□	20.0□	8□□	250□□
PDF 417	6.8□	5□□	95□□
□□□□	10.0□	5□□	110□□
□□□□	20.0□	10□□	150□□
□□□□1D□39	2.8□□□□0.071□□□□		
□□□□□□□□□□	4.8□□□□0.122□□□□		
□□	ABS + PC		
□□	95x65x155mm		
□□	160□		
□□□□□□	18.2X11.7X11.2cm		
□□□□□□	374□		

