

OCBS-T008

OCBS

OCBS	
Wavelength	650nm
Interface	KBW RS232 USB
OCBS	
Dimensions (mm)	140mm*83mm*75mm 157mm*98.3mm*100mm
Weight	282g; 379g
Material	OCBS
Material	
OCBS	
Accuracy	5.0 +/- 10
Resolution	275
Power	2W
Standards	CDRH IIa; IEC 60825-1
OCBS	
Operating Temp	0°C - 40°C
Storage Temp	-40°C - 70°C
Humidity	5-95% RH
Shock	1.2g
Vibration	450mm/s <sup>2</sup> 4844mm/s <sup>2</sup> 8000Ft/min 86111mm/min
OCBS	
Accuracy	5mm 20mm
Resolution	1500
Accuracy	360mm
Accuracy	+/- 50
Accuracy	25mm
Accuracy	0.216mm @ 13mil 100mm UPC / EAN
Resolution	5mil 38mm 10mm 64mm 7.8mil 60mm 0mm 152mm 10.4mil 80mm 0mm 190mm 13mil 100mm 0mm 216mm
Resolution	5mil
Accuracy	UPC/EAN/JAN, UCC/EAN 128, Code128, Code 39, Code 39 Trioptic, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code 93, Code 11, Code bar, MSI etc.

