

□□□□□□□□□□□□

□□□□OCBS -L011□

□□□

1□□□□□□□□□□□□

2□□□□□□□200□□□□/□□□□□□□□□□

3□□□□□□□□□□

4□□□□KBW□RS232□USB;

5□□□□□□□□□□□□□□□□

6□□□□□□□□□□

□□□

□□□□	
□□□□	□□□□□650-670nm□
□□□□□□	□□200□□□□
□□□□□	2.5□600mm□100□UPC / EAN□
□□□□□□□	□□□□
□□□□□	□PCS 0.9□□0.10mm□400□□
□□□□□□□□□□	30□□□□□□□□□□@ 650nm□
□□□□□	1/3000000
□□□□□□	UPC / EAN□□□□□□□□□□UPC / EAN□UCC / EAN128□□□□39□□□□39□ASCII□□□□39□□□□□□□□128□□□□128 □ASCII□codabar□□□2 of 5□□□2 of 5□□□93□MSI □□□□11□ATA□RSS□□□□□□2 of 5 ...
□□□□□	
□□□□□□□□	PS2□RS232□USB
□□□□	□□+ 5V +/- 5□
□□□□	100□□
□□□□□□	<40 mA
□□□□□	□□□□□□□□□□RS232□□□□
□□□□□	□□45°□□60°
□□□□	□165mm X□63mm X□87mm
□□□□	129□□□□□□□□□□
□□□□	□□□□
□□□□	□□□□□□
□□□□	
□□□□□□	0°C□40°C
□□□□□□	-40°C□60°C
□□□□□	□□□□□5□95□□□□□□□
□□□□□□	□□+/- 15KV□□□□□□□+/- 8KV□□□□□□

□□□□□	□□□□□1.5m□□□□□□□□
□□□	
EMI / RFI□	FCC A□□CE
□□□□□□	CDRH 2□□□□□



OCBS-L011





OCBS-L011





OCBS-L011





OCBS-L011





OCBS-L011



□OEM / ODM□

□□□□□□□□

▶ Company



▶ Certificates



▶ Payment



□□□□□□

· POS □□□□□□□□□□□□□□□□

· □□□□□□500 □□□□□□

· 1 □□□□□□□□□□ O2 □ Star ...

· □□163 □□□/□□□2600 □□□□□

· □□□□□□□□□□24 □□□□□□□

· □□12 □ OEM / ODM □□□□□□□□□□

· □□□□□□□□□□□□□□□□

· □□ ISO 9001 □ FCC □ CE □ Rohs □ Soncap □ SASO □ POA □ BIS □□□□□□□□

· □□□□□□□□□□□□□□□□□□□

· □□□□□□□□12 + 1 □□□□□□□□□□□□

· □□“□□□□□□”

· □□“□□□□□□□□□□□□□□□□” □□□□□□



