□□□□□□2□□□□□□□□□□□□□
□M / N□OCBP - 201□

□□□

1. USB□USB +□□□□□□
2.□□□□□□□□□
3.□□□□□□□□
4.□□ □□ □□□□□□□□□□
5. □□TSPL□ESC / POS□□
6.□□□□□□□□□□□□□□□□□

□□□

□□□□	□□□□
□□□	203DPI
□□	TSPL□ESC / POS
□□□□	□□ □□ □□□□□□□□□□ □□□□□HEX□1F 1B 1F 02 20 n 0D 0A□□□n = 31 / 30.dEFAULT ñ= 30□
□□□□	20-60mm□
□□□□□	MAX□101□□/□;□□□□50.8□□/□
□□	DRAM□ 256KB □□ 576KB
□□□□□	□□□□
□□□□□□	□□Icro□□
□□	USB orUSB +□□
□ □□□□	□□□□□□
□□	CODE128□EAN128□ITF□CODE39□CODE93□EAN13□EAN13 + 2□ EAN13 + 5□EAN8□EAN8 + 2□EAN8 + 5□CODABAR□POS TNET□ UPC-A□UPCA + 2□ UPCA + 5□ UPC-E□ UPCE + 2□ UPC-E + 5□ C POS T.□ MSI□ MSIC□PLESSEY□ ITF14□ EAN14 Qrcode□ DM□□□ PDF417
□□□□□□□□	□0°□90°270°□360°□□□□□1□10□; 0°□ □□90°□270°□360°
□□	□□PCX□BMP□□□□□□□□□FLASH□
□□□□	□□□□□□□□□□
□□□□	20□□□60□□
□□□□□	□□80□□
□□□□	□□25□□
□□□□	□□
□□□□	DC12V□3A
□□□□	5~45°C□□□□□20-80□□□□□□
□□	-40~55°C□□□□□≤93□□40°C□

ocom®
At your side
OCBP-201
ON LINE
ERROR
PAUSE
FEED
ISO
FC
CE
RoHS

Ocom®
At your side

OCBP-201

ISO FC CE RoHS

ocom®
At your side
OCBP-201
ISO
FC
CE
RoHS

OCOM®

At your side

OCBP-201

ISO FC CE RoHS

Ocom®

At your side

OCBP-201

Ocom®
At your side

OCBP-201

ISO FC CE RoHS

OCOM®

At your side

OCBP-201

ISO FC CE RoHS

OCOM®

At your side

OCBP-201

ISO FC CE RoHS

□□□□□

OCOM □□□□□□□□□□POS□Auto-ID□□□□□□□□□□□ □□□□500□□□□□□□□□□□□□□□□□□□□□□

OCOM□□□□□□□□ □□□□□□□□□□□□□□DOT□□□□□□□□□□□□□□□□□□□□□□□POS□□□□□□POS□□□□□□□□□□□□□□□□□□□