

2

M / N OCBP - 201

□□□

1. USB□USB +□□□□□□
- 2.□□□□□□□□
- 3.□□□□□□
- 4.□□ □□ □□□□□□□□
5. □□TSPL□ESC / POS□□
- 6.□□□□□□□□□□□□□□

□□□

□□□□	□□□□
□□□	203DPI
□□	TSPL□ESC / POS
□□□□	□□ □□ □□□□□□□□□□ □□□□□HEX□1F 1B 1F 02 20 n 0D 0A□□□□n = 31 / 30.dEFAULT ñ= 30□
□□□□	20-60mm□
□□□□□□	MAX□101□□/□;□□□□□50.8□□/□
□□	DRAM□ 256KB □□ 576KB
□□□□□□	□□□□□
□□□□□□□□	□□Icro□□
□□	USB orUSB +□□
□ □□□□□	□□□□□□□
□□	CODE128□EAN128□ITF□CODE39□CODE93□EAN13□EAN13 + 2□ EAN13 + 5□EAN8□EAN8 + 2□EAN8 + 5□CODABAR□POS TNET□ UPC-A□UPCA + 2□ UPCA + 5□ UPC-E□ UPCE + 2□ UPC-E + 5□ C POS T.□ MSI□ MSIC□PLESSEY□ ITF14□ EAN14 Qrcode□ DM□□□□ PDF417
□□□□□□□□	□0°□90°270°□360°□□□□□□1□10□; 0°□ □□90°□270°□360°
□□	□□PCX□BMP□□□□□□□□□□FLASH□
□□□□	□□□□□□□□□□
□□□□	20□□□□60□□
□□□□□□	□□80□□
□□□□	□□25□□
□□□□	□□
□□□□	DC12V□3A
□□□□	5~45°C□□□□□□20-80□□□□□□□□
□□	-40~55°C□□□□□□≤93□□40°C□



OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201



