

PDF417OCBS-2103

OCBS-2103

Features

- 100% compliance with IOTC 0370 CHIP
- 640x480 CMOS
- RS-232 9.6/115.2Kbps, USB 1.1, HID-KBW, HID-POS
- 2D: PDF417, Data Matrix, QR
- 1D: EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Coda bar, Code 128 (Include FNC1 FNC2 FNC3 subset), Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Data bar (RSS-Expand, RSS-Limited, RSS-14), Code 39 (Include Code 39 FULL ASCII), Code 11, MSI-Plessey
- ≥10
- LED
- 10
- ≥30
- 68°/42°/54°
- 0 - 100000 LUX
- 1 W
- DC 5V/0.5A, AC 100/240V/50/60HZ
- 127.3x111.5x94mm
- 300
- -10°C ~ +50°C
- -20°C ~ +60°C
- 5% ~ 95% RH
- uTools
- FCC 15B, CE EMC B

Specifications

Model			OCBS-2103
Chip			IOTC 0370 CHIP
Resolution			640x480 CMOS
Interface			RS-232 9.6/115.2Kbps, USB 1.1, HID-KBW, HID-POS
Barcode	2D	PDF417, Data Matrix, QR	
	1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Coda bar, Code 128 (Include FNC1 FNC2 FNC3 subset), Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Data bar (RSS-Expand, RSS-Limited, RSS-14), Code 39 (Include Code 39 FULL ASCII), Code 11, MSI-Plessey	
Sensitivity			≥10
Light Source			LED
Illumination			10
Field of View			≥30
Viewing Angle			68°/42°/54°
Ambient Light			0 - 100000 LUX
Power Consumption			1 W
Power Supply			DC 5V/0.5A, AC 100/240V/50/60HZ
Dimensions			127.3x111.5x94mm
Weight			300
Operating Temperature			
Storage Temperature			-10°C ~ +50°C
Operating Humidity			-20°C ~ +60°C
Storage Humidity			5% ~ 95% RH
Software			uTools
Certification			FCC 15B, CE EMC B