□□□□/□□/□□□□4□□□□□□□□□□□□

□M / N□OCBP -007-U□

□□□**1**□

□□□□□□□□□□

32□RISC CPU

8MB SDRAM□4MB□□

□□□□□

203 dpi□□□

102mm□4'''□/ s□□□□□

108mm□□□□

20-112mm□0.78“-4.4”□□□ □edia□□

2.Parameters□

□□	
□□□	8□/ mm□203DPI□
□□□□	□□□□
□□□□□□	102□□□4“□/ S.
□□□□□□	108□□□4.25□□□
□□□□□□	2286□□□90□□□
□□□□	□□□□□□□□□□□□□□□□□□□□□□
□□□□	20-112mm□0.78“-4.4”□
□□□□	0.06□0.16□□□□2.36□6.3mil□
□□□□	10□2286□□□0.4 '' '' □90 '' ''□
□□□□□	□□127□□□5□□□□□□□
□□	□□□□
□□□□	240□□□w ^□×211□□□H□×166□□ □d□
□□	2.15□□
□□□	32□RISC CPU
□□	4MB□□□8MB SDRAM□□□□□□□□□SD□□□□□□□4 GB
□□	USB 2.0
□□□□	8□□□□□□□□□□□Windows□□□□□□□□□
□□	1D□□□□Code 39□Code 93□Code 128UCC□Code 128 subsets A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□UPC 2□ 5□□□□□□MSI□PLESSEY□POS TNET□□□POS T.
	□□□□□PDF-417□Maxicode□DataMatrix□QR□
□□□□□□□□	0°□90°□180°□270°
□□□□	□□□5~40°C□25~85□□□□□□□□-40~60°C□10~90□□□□

3.Pictures□

Product Picture

Features

All-round show

Application Area

Parameter

Parameter	
Resolution	8 dots/mm(203DPI)
Printing method	Direct Thermal
Max. print speed	102 mm (4")/S
Max. print width	108 mm (4.25")
Max. print length	2286 mm (90")
Media type	Continuous, gap, black mark, fan-Fold and punched hole
Media width	20-112mm (0.78"-4.4")
Media thickness	0.06~0.16mm(2.36~6.3mil)
Label length	10~2,286mm(0.4"~90")
Label roll capacity	127 mm (5") OD (outside w ound)
Enclosure	Double-w alled plastic
Physical dimension	240 mm (W) × 211 mm (H) × 166 mm （D)
Weight	2.16kg
Processor	32-bit RISC CPU
Memory	4MB Flash Memory, 8MB SDRAM, SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0
Internal fonts	8 alpha-numeric bitmap fonts, Window s fonts are dow nloadable from softw are.
Barcode	1D bar code： Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
	2D bar code： PDF-417, Maxicode, DataMatrix, QR code
Font and barcode rotation	0°、90°、180°、270°
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing; Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

Production Line

4.FAQ□

1□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□

2□□□□□□□&□□
□□□□□□□□□□□□□□□□□□□□□□
□□□

□□□□□t / t□western uion□paypal□□□□□□□□□□□□□□□□□□□□□□□aliexpress□□□□□□
□□http□//www.aliexpress.com/store/403448□tracelog = minisite_CI□

3□□□□
OCOM□□□□□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□□□□500□□□□□□□□□□□□□□□□□□□100□□□□□□□□□□□□

□□□□□□□□□□□□□□12 + 1□□□□□□□□□□□□24□□□□□□;

□□□□30□□□□□□□□□□□□□□DOA□□ DOA□□□□□□□□□□□□□□

□□

4□□□□□
□□□□□□□□□□□□T / T□LC□Western Union□Escrow□□□□□□□□□□□□□□□□T / T□Western Union□Escrow□Paypal□
□□□□□□.Escrow□□□Alipay.com□□□□□□□□□□□□Moneybookers□Visa□MasterCard□□□□□□□□□□□□□□□□□□□□□□
□Maestro□Solo□Carte Bleue□Pos tePay□CartaSi□4B□Euro6000□

5.□□□□
OCOM Technologies Ltd.□□□TUV□□□POS□Auto-ID□□□□□□□□□□□□□□ OCOM□□□500□□□□□□□□□□1□□□□□
□□□□□□

OCOM□□□□□□□□□□□□□□□□□□□□□□□□□□□□POS□□□□□□□□□□□□□□□□POS□□□□□□□□□□□□□POS□□□□POS□□□
□□□CE□FCC□□□□□□□□

OCOM□□□□□□□□□□□□□□□□□□□□□□□□“□□□□□□□□□□□□□”□□□□□□□□□□□□□□□□□□□□□□□□□□□OEM / ODM□