

OCBP -004A / B

M / N OCBP -004A / B

OCBP

8 MB SDRAM 200 Mhz 32 RISC CPU 4 MB

OCBP

127 5

300 984' 25.4 1

Kiosk

TSPL-EZ TPLE TPLZ

	OCBP -004A	OCBP -004B
Resolution	8 / mm 203 DPI	12 / mm 300 DPI
Resolution	&	
Resolution	127 5	101.6 4
Resolution	108 4.25	104 4.09
Resolution	2794 110	1016 40
Resolution		
Resolution	20-112mm 0.78"-4.4"	
Resolution	0.06~0.254 mm 2.36~10 mil	
Resolution	10~2,794 0.39"~110"	10~1016 0.39"~40"
Resolution	127 5	
Resolution	300 67 mm 1" 40 mm~110 mm 1.6"~4.3"	
Resolution		
Resolution	234 194.8 302.5	
Resolution	3.1 6.83	
Resolution	32 RISC CPU	
Resolution	4MB Flash Memory	
Resolution	8MB SDRAM	
Resolution	SD 4 GB	
Resolution	USB2.0 RS-232 Centronics 10/100 Mbps 802.11 b / g / n	
Resolution		
Resolution	AC 100-240V 1A 50-60Hz	
Resolution	DC 24V 2.5A 60W	
Resolution	LED 1 1 1 LED 3	

□□□□	□□□□□□□□ position□□□□
	□□□□□□□□
	□□□□□□□□
	□□□□□□□□
□□□□	□□
□□□□	8□□□□□□□□□□ □□TTF□□□□
□□	1D□□□□Code 39□Code 93□Code 128UCC□Code 128□A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□ EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□□MSI□PLESSEY□POS TNET□□□□POS T □□□□□□PDF-417□Maxicode□DataMatrix□□□□□
□□	BIMAP□BMP□PCX□□□□256□□
□□□□□□□□	0°□90°□180°□270°
□□□□□□	TSPL□EPL□ZPL□DPL□
□□□□	□□□□5~40°C□25~85□□□□□ □□□□-40~60°C□10~90□□□□□
□□□□	FCC□CE□CCC□CB
□□□□	□□RoHS
□□	①Windows□□□□CD□;②□□□□□□□;③USB□□;④□□□□;⑤□□□□□□□□□□;⑥□□□□□□□□□□x 2,1.5"□□□□□x 2;⑦Ribbon□□x 2;⑧Ribbon□□□;⑨□□
□□□□	□□□□□□□□10/100 Mbps□RS-232□Centronics□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□0.06~0.19mm□ □□500000; 0.20~0.25mm□□□□200000
□□□□	□□□□□□□□□□OD□ 214□□□□8.4□□□□□25.4□□□□1□□□□□□□□□□□□□□ □□□□□□□□□□□□802.11 b / g / n□□□□□□□□□□□□□□□□□□□□□□□□RFID□□□□

Product show:



□□□□□

OCOM.com

