

□□□□□□□□□□

□□□□OCBS -L012□

□□□

1□□□□□□□□□□□□

2□□□□□□□200□□□□/□□□□□□□□□□

3□□□□□□□□□□

4□□□□KBW□RS232□USB;

5□□□□□□□□□□□□□□□□

6□□□□□□□□□□

□□□

□□□□	
□□□□	□□□□□650-670nm□
□□□□□□	□□200□□□□
□□□□□	2.5□600mm□100□UPC / EAN□
□□□□□□□	□□□□
□□□□□	□PCS 0.9□□0.10mm□400□□
□□□□□□□□□□	30□□□□□□□□□□@ 650nm□
□□□□□	1/3000000
□□□□□□	UPC / EAN□□□□□□□□□□UPC / EAN□UCC / EAN128□□□39□□□39□ASCII□□□□39□□□□□128□□□□128□ASCII□□ codabar□□□□2□5□□□□2□5□□□□93□MSI □□□□11□ATA□RSS□□□□□□□2□5 ...
□□□□□	
□□□□□□□□	PS2□RS232□USB
□□□□	□□+ 5V +/- 5□
□□□□	100□□
□□□□□□	<40 mA
□□□□□□	□□□□□□□□□□RS232□□□□
□□□□□	□□45°□□60°
□□□□□	□165mm X□63mm X□87mm
□□□□□	129□□□□□□□□□□
□□□□	□□□□
□□□□□	□□□□□□
□□□□	
□□□□□□	0°C□40°C
□□□□□□	-40°C□60°C
□□□□□	□□□□□5□95□□□□□□□
□□□□□□	□□+/- 15KV□□□□□□□+/- 8KV□□□□□□
□□□□□□	□□□□□□1.5m□□□□□□□□□□

□□□	
□□	CE □ ROHS
□□□□□□	IEC 2□□□□□



OCBS-L012





OCBS-L012





OCBS-L012





OCBS-L012





OCBS-L012





OCBS-L012



OCOM " " OEM / ODM

▶ Company



▶ Certificates



▶ Payment



□□□□□□□□

·POS□□□□□□□□□□□□□□□□□□□□

·□□□□□□500□□□□□□□□

·1□□□□□□□□□□□□O2□Star ...

·□□163□□□□/□□□2600□□□□□□

·□□□□□□□□□□24□□□□□□□□

·□□12□OEM / ODM□□□□□□□□□□□□

·□□□□□□□□□□□□□□□□□□

·□□ISO 9001□FCC□CE□Rohs□Soncap□SASO□POA□BIS□□□□□□□□□□

·□□□□□□□□□□□□□□□□□□□□□□

·□□□□□□□□12 + 1□□□□□□□□□□□□□□

·□□“□□□□□□□□”

·□□□“□□□□□□□□□□□□□□□□□□□□□□”□□□□□□□□



