

CCD

M / N OCBS-F1200

00

- ARM 32
- 3.3mil
-
- TTL- RS232 / USB / PS2
- 300/
- CCD

0000

FPC12pin 0.5



00	00	I / O	00
1	NC	-	000
2	VCC	-	00
3	GND	-	000
4	RX	00	TTL-RS232
5	TX	00	TTL-RS232
6	D- /	0000	USB_D- / PS2_
7	D + / HOST CLK	0000	USB_D + / PS2_HOST CLK
8	KB DATA	-	PS2_KB
9	000	00	000000
10	LED	00	000000
11	KB CLK	-	PS2_KB CLK
12	0	00	00000000000020ms 00 20ms0000000020ms00000000 0000000020ms

□□□

1. USB

2. RS232□□



□□

□□□□

□□	632nm LED□
□□□	□□ CCD□□□
□□□	ARM32□
□□□	≥4mil/0.1mm@PCS90%
□□ □□	3-50CM
□□□□	300 □□/□
□□ □□	□ □□□□□□□□□□□□□□□□□□ □□□±60°
□□□□	□□ ±30° □□□ ±60°
□□ □□	DC 3.3V-5V
□□	110□□□□□□□□;30□□□□□ □□□
□□□□□	≥25□
□□ □□□	100,000Lux □□□

□□ □□

EAN-8□EAN-13□ Codabar□CODE11□□□39□ □□93□□
□128□□□□□□GS1-128□GS1 Limited□GS1 □□□UPC-A□
UPC-E□ISBN / ISSN□ISBT□Interleaved 2 of 5□ □□2
□5□□□2□MSI□□□□□ ITF14□