

□□□□□□□□□□

□□□□ **ECD-410D** □

□□□

4□5□□□□□□□□□8□□□□□□□□□□

□□□□□□□□□□□□□□□□

9V□24V□□□

□□□□□□□□□□

□□□3□□□

□□□

□□	□□□□□0.8□□ SPCC□□□□□□□□□□□□
	□□□1.0mm SECC □□□□□
□□□□	□□□□ □□□85/84/84/85□□
	□□□□ □□□68/67/67/67/68□□
	□□□193□□; □□□59□□
□□	8□□□ □□□□82;□□□57;□□□46
□□	3□□
□□	12V 24V□□□
□□	□□□□□□□ □□□□□□□
□□	RJ11 / RJ12
□□	□□□
□□	6.5□□□□□□□7.0□□ □□□
□□□□	410□W□×415□L□× 100□□□□□□□□□10□□□

□□□□□



# ECD-410D



[www.ocominc.com](http://www.ocominc.com)





[www.ocominc.com](http://www.ocominc.com)





## Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

