

□□□□□□□□□□□□□□□□

□□□□□

□□□□□□□□□□□□□□□□  
 200scan/sec□□□□□□□□□□□□□□□□;  
 □□□□□□□□;  
 □□□□□□□□□□□□;  
 KBW□RS232□USB□□□□;  
 □□□□□□□□□□□□□□□□

□□□□□

□□□□	
□□□□	650nm□□
□□□□□□	□□200□□□
CPU	32□
□□□□	2.5□600□□□100□UPC / EAN□
□□□□□□	50□□@□60mm□220□□@200□□
□□□□□□□□	□□
□□□□	□□□□
□□□□	□3mil□□□□□□□/ 5MIL□□□□ □□
□□□□□□□□□□	30□□□□□□□□
□□□□□□	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code, GS1 DataBar (RSS)□□
□□□□	±65°□□□□□; ±60°□□□□□; ±42°□□□□□
□□□□	
□□□□□□□□	PS2□RS232□USB□□□□
□□□□	5V DC±5□
□□□□	85□□□□□□□□; 100□□□□□
□□□□	□□□□LED
□□□□	ABS + PC
□□□□□□	156 * 68 *83□□□□□*□*□□
□□□□	235□
□□□□	□□□□□
□□□□	
□□□□□□	0°C□45°C
□□□□□□	-40°C□60°C
□□□□	5□-90□ □□□□□□
□□□□□□	□□+ /-15kV□□□□□□ □□□□+ /-8KV
□□□□	0□100,000 LUX
□□□□□□	□□□□□□1.5□□□□□□□□□ □□
□□□□	EN60825-1□1□

□□□□□□□□

