

OEM  
OCBS-LA04

OCBS-LA04

|                       |   |
|-----------------------|---|
| Wavelength            | 650-670nm   |
| Beam Diameter         | 100   |
| Beam Power            | 2.5mW 600nm 100mW UPC / EAN   |
| Beam Quality          |   |
| Beam Divergence       | 0.10mrad 4MIL PCS 0.9   |
| Beam Modulation       | 20kHz @ 650nm   |
| Beam Encodings        | UPC / EAN UPC / EAN UCC / EAN128 39 39 ASCII 3 trioptic 128 128 ASCII 2 5 2 5 93 MSI 11 ATA RSS 2 5 ... |
| Interface             | PS2 RS232 USB   |
| Power Supply          | DC + 5V ± 5%  |
| Power Consumption     |   |
| Operating Temperature | < 40°C  |
| Storage Temperature   | RS232   |
| Viewing Angle         | 45° 60°   |
| Dimensions            | L165.42mm X W69.72mm X H89.67mm   |
| Weight                | 140g  |
| Material              |   |
| RoHS                  |   |
| Operating Temperature | 0°C 50°C  |
| Storage Temperature   | -40°C 70°C  |
| Humidity              | 5% 95%  |
| ESD Protection        | +/- 15kV +/- 8KV  |
| Shock Resistance      | 1.5g  |
| EMC                   |   |
| EMI / RFI             | FCC A CE  |
| Regulatory            | CDRH 2  |

OCBS-LA04

XXXXXXXXXX

OCBS-LA04

OCBS-LA04 Information

OCBS-LA04