

OCPP 58

OCPP -58X



OCPP

OCPP -58X

OCPP

OCPP

OCPP

OCPP

OCPP

OCPP LOGO

OCPP

OCPP pos

OCPP

□□		□□
□□□□	□□□□	□□
	□□□□	48□□
	□□□	384□/□□8□/ mm□203dpi
	□□□□	90mm /□
	□□□□	USB□□□
	□□□	3.75 mm□□□□□□□□□□
	□□	□□A□32□□□/□ □□B□42□□□/□ □□□□□□□16□
	□□	□□GB2312□□□□□□
□□□□□	□□□□	ANK□□□□□A□1.5×3.0mm□12×24□□ □□B□1.1×2.1mm□9×17□□□□/□□□□□3.0×3.0mm □24×24□□
	□□	UPC-A / UPC-E / JAN13□EAN13□/ JAN8□EAN8□CODE39 / ITF / □□/ CODE93 / CODE128
□□□□	□□□□	□□□□□□□□□□
□	□□	□□
	□□	57.5±0.5□□
	□□	≤60□□
	□□□□	□□□□□□□□□□
□□□□	□□	□□/ POS
□□	□□□□□	□□□AC 100V-240V□50-60Hz □□□DC 12V / 2.6A
	□□□□	□□12V / 1A
□□	□□□□□	32 KB
	NV□□	64 KB





OCPP-58X





OCPP-58X





▶ Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant

