

58

OCPP - M12



-
-
- WindowsJavaLinuxAndroidIOS
- AndroidSDKIOS
- 57 * 40
- 8
- 7AndroidApple
- 7.4V1500mA
- 90/
- 50km
-
- ESC / POS

	ESC / POS
	48
	90/
	8/ mm203dpi
	12x24 / 24x24
	32/ 16
	1.5 x 3.0 mmx/3.0x3.0mmx

外形寸法	58.0±0.1mm x 40.0mm
重量	0.06~0.08g
材質	樹脂/銅
接続	USB
容量	256KB
動作電圧	9V DC / 2A
動作電圧	7.4V DC
動作温度	-10~50℃ 保存温度10~90℃
動作湿度	-20~70℃ 保存湿度5~95%
データ形式	30 ASCII
表示	“1234”











□□□□□□□□



5/5

```
000000000000000000000000000000000000 Mini0000000000TAXI00000000pos0000  
000000000000000000000000000000Mini0000000000
```

55

OCOM□□□□□POS□Auto-ID□□□□□□□□□□500□□□□□□□□□□□□□□□□

OCOM DOT POS POS
ISO CE FCC BIS

2007 6 OCOM ISO9001 2008 159 2300
50 02 Equicom

OCOM " " OEM / ODM

1000000000

Strong R&D, Efficient and Flexible Manufacturing



Professional Marketing and Sales Team



□□□□□□□□

```
·POS[0][0][0][0][0][0][0][0][0][0][0][0][0][0][0][0];
```

• □□□□□□500□□□□□;

·■■■■■■■■■■02■Star

·2600□□□□□163□□□;

·□□□□□□□□24□□□□□□□□;

- 12 OEM / ODM
-
- ISO 9001 FCC CE Rohs Soncap SASO POA BIS
- MOQ
- 12 + 1
- “
- “”



2.&

3.

□□□□□□□□□□□□□□□□