

OCPP 58

OCPP - M12



OCPP

OCPP 58

OCPP 58, Windows, Java, Linux, Android, iOS

OCPP 58, Android, SDK, iOS

57 * 40

OCPP 58, 8

OCPP 58, Android, Apple

7.4V, 1500mA

OCPP 58, 90

50km

OCPP 58

ESC / POS

OCPP

OCPP	OCPP
OCPP	ESC / POS
OCPP	48
OCPP	90
OCPP	8 / mm 203dpi
OCPP	12x24 / 24x24
OCPP	32 / 16
OCPP	1.5 x 3.0 mm x / 3.0x3.0mm x

尺寸	58.0±0.1mm x40.0mm
厚度	0.06~0.08mm
重量	0.005g/0.001g
接口	USB
容量	256KB
供电电压	9V DC / 2A
输出电压	7.4V DC
工作温度	-10~50℃存储10~90℃
存储温度	-20~70℃湿度5~95%
数据格式	可自定义30个ASCII
字符	可自定义“1234”



产品规格



应用案例

产品广泛应用于Mini、TAXI、pos、Mini等场景。



XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXX