

□□□□□□□□□□□□□□□□2d

□□□□OCBS -2013□



### Feautre□

□□□□□□□;

1MP□□□1MP□1280 \* 800□;

□□□□□;

□□□□1D□2D□□□□□□□;

□□□□□□□□□□□□□□□;

4mil□□□□□□□□;

□□□□□□□;

□□ASCII□□□□□□□□□□□

□□□

□□	
□□	□□LED
□	□□□

□□	□□□
□□□	□□LED□□□□□□
□□□□	
□□□	CMOS
□□□	1280 * 800,256□□
□□□□□□	13mil UPC 40cm / s
□□□□	□□50□;□□20□
□□	≥4mil
□□□□	1D UPC-A□UPC-E□UPC-E1□EAN-13□EAN-8□ISBN□Bookland EAN□ISSN□Code 39□Code 39□ASCII□Code 32□Trioptic Code 39□Interleaved 2 of 5□Industrial 2 of 5□Discrete of of 2□Matrix 2 of 5□Codabar□NW7□Code 128□UCC / EAN 128□GS1-128□ISBT 128□Code93□Code 11□USD-8□ MSI / Plessey
	2D PDF417□MicroPDF417□QR Code□DataMatrix□Han Xin Code□Aztec Code□GS1 Com pos ite
□□	□□39□5mil□□50mm~120mm □□39□10mil□□25mm~250mm UPC / EAN□13mil□□20mm~320mm □□□□□7.5mil□□63mm~150mm PDF417□6.6mil□□62□145□□
□□□	□□±45°@ 0°Roll□0°Skew □□±30°@ 0°□□□0°□□ □□±45°@ 0°Roll□0°Skew
□□	
□□	USB□USB□□COM□□□□□□□□
□□□□	3.3v~5v DC
□□□□	2.0w□400mA□
□□□□	2.5w□450mA□
□□□□□	□□5.5V 1A
LED CLASS	□□
□□□□	
□□□□	-20□□□□+ 60□□□□-4□□□□144□□□□
□□□□	-30□□□□+ 70□□□□-22□□□□158□□□□
□□	5□ - 95□□□□□□
□□□	1.5□□5.0□□□□□□□□□□
IP□	IP54
□□□□	□□□□□□□□□□









OCOM " " OEM / ODM

## ▶ Company



## ▶ Certificates



## ▶ Payment







