

Pos



M / N OCBP -008

200mm / s8" / s

300m 214mm 8.4" OD

8MB 8MB SRAM

TSPL / EPL / ZPL / DPL

USB2.0

Bartender & Windows

|  |               |
|--|---------------|
|  | 8 / mm 203dpi |
|  |               |
|  | 200 8 /       |

|          |                                                                                                                                                                                                                              |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 重量       | 104g±4.09g                                                                                                                                                                                                                   |
| 寸法       | 1778mm±70mm                                                                                                                                                                                                                  |
| 材質       | ABS樹脂                                                                                                                                                                                                                        |
| 寸法       | 25.4~115mm                                                                                                                                                                                                                   |
| 寸法       | 0.06~0.25mm                                                                                                                                                                                                                  |
| 寸法       | 10~1778mm                                                                                                                                                                                                                    |
| 寸法       | 127mm±5mm                                                                                                                                                                                                                    |
| 材質       | ABS樹脂                                                                                                                                                                                                                        |
| 寸法       | 246mm×223mm×204mm                                                                                                                                                                                                            |
| 寸法       | 2.47mm                                                                                                                                                                                                                       |
| CPU      | 32bit RISC CPU                                                                                                                                                                                                               |
| メモリ      | 8MB ROM 8MB SDRAM Mro SDメモリー 4 GB                                                                                                                                                                                            |
| インターフェース | USB 2.0 / TF;<br>RS-232 / / WIFI /                                                                                                                                                                                           |
| バーコード    | 1D Code 39 Code 93 Code 128 UCC Code 128 A B C<br>Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A<br>UPC-E EAN<br>UPC 2 5 MSI PLESSEY POS TNET POS T GS1<br>DataBar Code 11<br>2D PDF-417 Maxicode DataMatrix QR Aztec |
| 機能       | ①RS-232 2400-115200 bps ② ③WiFi ④<br>⑤ ⑥LCD/ LED                                                                                                                                                                             |
| 認証       | FCC CE CB CCC                                                                                                                                                                                                                |
| 動作温度     | 10~50°C 14~122°F 10~90<br>40~60°C -40~140°F 10~90                                                                                                                                                                            |











□□□□□□□□



## ▶ Company



## ▶ Certificates



## ▶ Payment



□□□□□□□□

·POS□□□□□□□□□□□□□□□□□□;

·□□□□□□500□□□□□□;

·□□□□□□□□□□O2□Star .....

·2600□□□□□□163□□□;

·□□□□□□□□24□□□□□□□□;

·□□12□OEM / ODM□□□□□□□□;

·□□□□□□□□□□□□□□□□;

·□□□□□□□□ISO 9001□FCC□CE□Rohs□Soncap□SASO□POA□BIS□□;

·□□□□□□□□MOQ□□□□□□□□□□□□;

·□□12 + 1□□□□□□□□□□□□□□□□;

·□□“□□□□□□”

·□□“□□□□□□□□□□□□□□□□□□”□□□□□□□□



