

2d rs232

M / N OCBS -2012



Feautre

;

;

;

;

5mil;

;

;

□□□□		
□□□	640 * 480	
□□	LED□617 nm±10 nm□	
□□	0~100,000 LUX	
□□□□	□□360°\□□±60°\□□±65°	
□□□□	300scan /□	
□□	2D	DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR□□Standard 2 of 5□Telepen□TLC 39□□
	1D	□□□□Pos□□Aztec□BPO□□□□Pos□□Codabar□Codablock□Code 11□Code 39□Code 93□Code 128 / EAN128□Dutch Post□EAN.UCC Com pos ite□Interleaved 2 of 5□Japan Pos t□Planet□Plessey Code□Pos tnet□RSS□UPC / EAN□□
□□	≥5mil□□□□□□□□	
□□	360°	
□□	65°	
□	75°	
□□□□		
□□	RS232 / USB / USB□□COM	
□□	DC 5 V±5□	
□□	190 mA□□□□	
□□	1.5□	
□□	165□	
□□	170□□x 60□□x95□□	
□□□□		
□□□□	-5°C□65°C	
□□□□	-20°C□70°C	
□□	5□ - 95□□□□□□	
□□□	□150□□□□□□□□	

□□□□□









02 Equicom

OCOM " " OEM / ODM

▶ Company



▶ Certificates



▶ Payment



□□□□□□□□

·POS□□□□□□□□□□□□□□□□□□;

·□□□□□□500□□□□□□;

·□□□□□□□□□□O2□Star

·2600□□□□□□163□□□;

·□□□□□□□□24□□□□□□□□;

·□□12□OEM / ODM□□□□□□□□;

·□□□□□□□□□□□□□□□□;

·□□□□□□□□ISO 9001□FCC□CE□Rohs□Soncap□SASO□POA□BIS□□;

·□□□□□□□□MOQ□□□□□□□□□□□□;

·□□12 + 1□□□□□□□□□□□□□□□□;

·□□“□□□□□□”

·□□“□□□□□□□□□□□□□□□□□□”□□□□□□□□



