

□□□□□□□□□□□□□□□□□□□□



□M / N□OCBP -008□

□□□

□□□□□□□□□□

200mm / s□8" / s□□□□□□□□□□□□□□□□;

300m□□□□□□□214mm□8.4"□OD□□□□□□□□;

8MB□□□8MB SRAM□□

□TSPL / EPL / ZPL / DPL□□□□□□□□□□□□□□□□;

□□USB2.0□□

Bartender□□□□□□& Windows□□□□□□□□;

□□□□□

□□□	8□/ mm□203dpi□
□□□□	□□□/□□□
□□□□□□	200□□□8□□□/□
□□□□□□	104□□□4.09□□□

重量	1778g
寸法	幅×高さ×奥行き
幅	25.4~115mm
高さ	0.06~0.25mm
奥行き	10~1778mm
材質	ABS
色	ABS
寸法	246mm×223mm×204mm
重量	2.47kg
CPU	32bit RISC CPU
メモリ	8MB ROM / 8MB SDRAM / Micro SD / 4GB
接続	USB 2.0 / TF; RS-232 / WiFi /
バーコード	1D Code 39 / Code 93 / Code 128 UCC / Code 128 A / B / C Codabar / Interleaved 2 of 5 / EAN-8 / EAN-13 / EAN-128 / UPC-A / UPC-E / EAN UPC 2 / 5 / MSI / PLESSEY / POS TNET / POS T / GS1 DataBar / Code 11 2D PDF-417 / Maxicode / DataMatrix / QR / Aztec
機能	①RS-232 2400-115200 bps ② ③WiFi ④ ⑤ ⑥LCD / LED
認証	FCC / CE / CB / CCC
動作温度	10~50°C / 14~122°F / 10~90%
保存温度	-40~60°C / -40~140°F / 10~90%











□□□□□□□□



## ▶ Company



## ▶ Certificates



## ▶ Payment





